

TOOLS PP/PET STRAP



FRICTION-WELD JOINT KOS 13

KOS 13 with its simple handling and intuitive operation, is extremely low weight, purely manual operation, is for mobile and occasional use. The applications are versatile; The purely mechanical operation as well as the single-lever technology for tensioning and joining make these tools the ideal choice for beginners who demand a cost-effective solution.

Technical Data

Kind of drive (tensioning)	Manually
Kind of drive (sealing)	Manually
Dimensions	320 x 65 x 165 mm (L x W x H) 12.6 x 2.6 x 6.5" (L x W x H)
Weight	2.3 kg 5.1 lb

Strap/Joint

Type of strap	Plastic strap
Strap	PP PET
Strap width	12 - 13 mm 0.472 - 0.512"
Strap thickness	0,40 - 0,70 mm 0.016 - 0.028"
Kind of seal	Seal-joint (single notch)
Sealing strength (depending on strap quality, strap dimensions)	approx. 65% of the strap breaking load

Application

Strapping of flat packages (e.g. packages, palletized goods) for mobile use.

Factory Address

Plot No. G28 & G29, General Park IP,
Sultanpur Medical Devices Park,
Telangana 502 319

Corporate Address

Shantha Jubilee, Jubilee Enclave, HITEC City,
Hyderabad, Telangana 500 081

Contact +91 93939 22442

E-mail info@acmeirm.com

Website www.mvsips.com