

STEEL STRAPPING TOOL



SEAL-LESS JOINT L221

L221 allows maximum flexibility when strapping with steel straps; it has settings for the strap widths 13-19 mm without the need to obtain more accessories. It is suitable for a wide variety of mobile applications and is highly accommodating with intuitive operation, easy handling, and it is light weight (3.5 kg) and completely needle bearing mounted.

Technical Data

Kind of drive (tensioning)	Manually
Tension force	up to approx. 5,000 N
Kind of drive (sealing)	Manually
Dimensions	500 x 100 x 150 mm (L x W x H) 19.7 x 3.9 x 5.9" (L x W x H)
Weight	3.5 kg 7.716 lb

Strap/Joint

Type of strap	Steel strap
Strap	Automatenband up to approx. 900 N/mm ² tensile strength
Strap width	13, 16, 19 mm 1/2" ; 5/8" ; 3/4"
Strap thickness	0.40 - 0.60 mm 0.016 - 0.024"
Kind of seal	Sealless-joint
Sealing strength (depending on strap quality, strap dimensions)	information currently not available

Minimum Bearing Area

Flat package	150 mm 5.9"
--------------	-------------

Application

Strapping of flat packages (e.g. palletized goods) for mobile use.
--

Factory Address

Plot No. G28 & G29, General Park IP,
Sultanpur Medical Devices Park,
Telangana 502 319

Corporate Address

Shantha Jubilee, Jubilee Enclave, HITEC City,
Hyderabad, Telangana 500 081

Contact +91 93939 22442

E-mail info@acmeirm.com

Website www.mvsips.com