



FRICITION-WELD JOINT TA 750

The TA 750 is the absolute top-of-the-range model in the TA family – with performance values that are second to none in the battery-powered hand-held segment. Other advantages of TITAN hand-held tools are the excellent handling properties of the TA series, and the extremely simple and intuitive operation using two buttons.

Technical Data

Kind of drive (tensioning)	Electric
Tension force	2,700 - 8,000 N (adjustable)
Kind of drive (sealing)	Electric
Power supply system	36 V / 2.0 Ah / 72 Wh
Strap feeding speed	12 m/min. 39.4 ft/min.
Dimensions	300 x 150 x 200 mm (L x W x H) 11.8 x 5.9 x 7.9" (L x W x H)
Weight	6.4 kg 14.1 lb
Handarm vibration	2.2 m/s ²
Noise level	81 dB (A)

Strap/Joint

Type of strap	Plastic strap
Strap	PP PET
Strap width	19 mm 3/4" 25, 32 mm 1" ; 1 1/4"
Strap thickness	0,80 - 1,40 mm 0.031 - 0.055" 1,00 - 1,30 mm 0.039 - 0.051"
Kind of seal	Friction-weld joint
Sealing strength (depending on strap quality, strap dimensions)	approx. 75% of the strap breaking load

Application

Strapping of flat packages (e.g. palletized goods) for mobile use.

Factory Address

Plot No. G28 & G29, General Park IP,
Sultanpur Medical Devices Park,
Telangana 502 319

Corporate Address

Shantha Jubilee, Jubilee Enclave,HITEC City,
Hyderabad, Telangana 500 081

Contact +91 93939 22442

E-mail info@acmeirm.com

Website www.mvsips.com