

# STEEL STRAPPING TOOL



## CRIMP JOINT (DOUBLE NOTCH) DCR

The DCR is a hand-held double crimping tool for Lifting & Lashing segment. The steel straps are first tensioned with the PLC and then the DCR sealer is used; The combination of PLC and DCR holds it all together for you.

### Technical Data

Kind of drive (sealing)	Pneumatic
Seal (Type)	NCR
Dimensions	300 x 370 x 350 mm (L x W x H) 11.8 x 14.6 x 13.8" (L x W x H)
Weight	11 kg 24.3 lb
Air pressure	max.7 bar flow pressure
Air consumption(sealing)	10 NI / Crimp stroke

### Strap/Joint

Type of strap	Steel strap
Strap	MEGABAND® special
Strap width	32 mm 1 1/4"
Strap thickness	0.80 mm (for H-strap) 1.12 mm (for HH-strap) 1.27 mm (for HHH-strap) 1.45 mm (for HHH-M-strap) 0.031" (for H-strap) 0.044" (for HH-strap) 0.050" (for HHH strap) 0.057" (for HHH-M-strap)
Kind of seal	Crimp-joint (double notch)
Sealing strength (depending on strap quality, strap dimensions)	up to 85 - 95% of the strap breaking load

### Application

Lashing & Lifting: for load securing for rail and sea transport  
Strapping of e.g. steel coils, wood or cellulose, etc.

#### Factory Address

Plot No. G28 & G29, General Park IP,  
Sultanpur Medical Devices Park,  
Telangana 502 319

#### Corporate Address

Shantha Jubilee, Jubilee Enclave, HITEC City,  
Hyderabad, Telangana 500 081

Contact +91 93939 22442

E-mail [info@acmeirm.com](mailto:info@acmeirm.com)

Website [www.mvsips.com](http://www.mvsips.com)