

STEEL STRAPPING TOOL



SEAL JOINT (DOUBLE NOTCH) DPZ-L

Fabulously executes two functions at a single push of a button, the DPZ-L joins and generates two notches in the seal. This self-contained double notching process guarantees the highest degree of joint reliability and ease. DPZ-L is a proven for maximum reliability in heavy-duty bandage applications like the PR33, the tensioner matching the SPZ-L.

Technical Data

Kind of drive (sealing)	Pneumatic
Seal (Type)	RSK, RSL
Dimensions	340 x 150 x 285 mm (L x W x H) 13.4 x 5.9 x 11.2" (L x W x H)
Weight	4.5 kg 9.9 lb
Air pressure	max. 6 bar flow pressure

Strap/Joint

Type of strap	Steel strap
Strap	Automatenband MEGABAND®
Strap width	19, 25 mm (Serie 1) 32 mm (Serie 2) 3/4" ; 1" (series 1) 1 1/4" (series 2)
Strap thickness	0.80 - 1.00 mm (for Automatenband) 0.80 mm (for MEGABAND®) 0.031 - 0.039" (for Automatenband) 0.031" (for MEGABAND®)
Kind of seal	Seal-joint (double notch)

Application

Strapping of packages and palletized goods with small contact surfaces.

Factory Address

Plot No. G28 & G29, General Park IP,
Sultanpur Medical Devices Park,
Telangana 502 319

Corporate Address

Shantha Jubilee, Jubilee Enclave, HITEC City,
Hyderabad, Telangana 500 081

Contact +91 93939 22442

E-mail info@acmeirm.com

Website www.mvsips.com