

STEEL STRAPPING TOOL



SEAL-LESS JOINT HKE-HD

HKE-HD is a special tool for high-performance straps. As compared to the HKE-L, to master the heavier loads, HKE-HD has a voluminous body with longer levers that makes the job easier. The typical HKE advantages are retained in the HD version and the sealless joint with three notches is particularly suitable for flat packages.

Technical Data

Kind of drive (tensioning)	Manually
Tension force	up to approx. 6,000 N
Kind of drive (sealing)	Manually
Dimensions	570 x 130 x 190 mm (L x W x H) 22.4 x 5.1 x 7.5" (L x W x H)
Weight	4.2 kg 9.3 lb

Strap/Joint

Type of strap	Steel strap
Strap	Automatenband up to approx. 900 N/mm ² tensile strength MEGABAND® up to approx. 1.100 N/mm ² tensile strength
Strap width	19 mm 3/4"
Strap thickness	0,60 - 0,80 mm 0.024 - 0.031"
Kind of seal	Sealless-joint
Sealing strength (depending on strap quality, strap dimensions)	to approx. 75% of the strap breaking load

Minimum Bearing Area

Flat package	150 mm 5.9"
--------------	-------------

Application

Strapping of flat packages (e.g. palletized goods) for mobile use.
--

Factory Address

Plot No. G28 & G29, General Park IP,
Sultanpur Medical Devices Park,
Telangana 502 319

Corporate Address

Shantha Jubilee, Jubilee Enclave,HITEC City,
Hyderabad, Telangana 500 081

Contact +91 93939 22442

E-mail info@acmeirm.com

Website www.mvsips.com