

# STEEL STRAPPING TOOL



## SEAL JOINT (DOUBLE NOTCH) HR 32

The Portable HR 32 is robust, light weight, and manually operated. It's especially used for the seals that the TITAN sealer HV joins, strapping circular and flat packages to perfection.

### Technical Data

Kind of drive (sealing)	Manually
Seal (Type)	RSK, RSL
Dimensions	450 x 110 x 200 mm (L x W x H) 17.7 x 4.3 x 7.9" (L x W x H)
Weight	3.9 kg 8.6 lb

### Strap/Joint

Type of strap	Steel strap
Strap	Automatenband MEGABAND®
Strap width	19, 25, 32 mm 3/4" ; 1" ; 1 1/4"
Strap thickness	0.80 - 1.00 mm (for Automatenband) 0.80 mm (for MEGABAND®) 0.031 - 0.039" (for Automatenband) 0.031" (for MEGABAND®)

### Application

Strapping of round and flat packages (e.g. sectional steel, bundles, pipes, coils, etc.) for mobile use.

#### Factory Address

Plot No. G28 & G29, General Park IP,  
Sultanpur Medical Devices Park,  
Telangana 502 319

#### Corporate Address

Shantha Jubilee, Jubilee Enclave,HITEC City,  
Hyderabad, Telangana 500 081

Contact +91 93939 22442

E-mail [info@acmeirm.com](mailto:info@acmeirm.com)

Website [www.mvsips.com](http://www.mvsips.com)