

STEEL STRAPPING TOOL



SEAL JOINT (DOUBLE NOTCH) PLC

A pure tensioner delivering highest force for extreme tensioning. It is used in conjunction with SCR or DCR sealers using crimp seals that allow controlled slipping of the strap in the seal, also serving as shock absorbers.

Technical Data

| | |
|------------------------------|---|
| Kind of drive (tensioning) | Pneumatic |
| Tension force | 20,000 N |
| Dimensions | 400 x 130 x 140 mm (L x W x H) 15.7 x 5.1 x 5.5" (L x W x H) |
| Weight | 8 kg 17.6 lb |
| Air pressure | max. 6 bar flow pressure |
| Air consumption (tensioning) | 10 NI / s |

Strap/Joint

| | |
|-----------------|------------------------------------|
| Type of strap | Steel strap |
| Strap | MEGABAND® special |
| Strap width | 32 mm 1 1/4" |
| Strap thickness | 0.80 - 1.45 mm 0.031 - 0.057 in |

Application

Lashing & Lifting: for load securing for rail and sea transport Strapping of e.g. steel coils, wood or cellulose, etc.

Factory Address

Plot No. G28 & G29, General Park IP,
Sultanpur Medical Devices Park,
Telangana 502 319

Corporate Address

Shantha Jubilee, Jubilee Enclave, HITEC City,
Hyderabad, Telangana 500 081

Contact +91 93939 22442

E-mail info@acmeirm.com

Website www.mvsips.com