

SHAPE AND COMPOSITE POLYESTER STRAPS

Shock resistant. Versatile. Highly tensile.



Highlights

Maximum Protection:
Extremely reliable for securing loads in diverse strapping and lashing applications.

Application Versatility:
Flexible design ensures smooth tension flow and adaptability for all uses.

Operating Efficiency:
Resistant to temperature variations and moisture.

Unparalleled Performance:
Excellent elongation recovery offers high resistance to shock and impact loads.

Features and Benefits



High resistance to shock and impact loads



Excellent elongation recovery properties



Intact in extreme weather conditions



Reliability & Flexibility with Buckle mechanism



Soft material, easy and safe to use



High tenacity for various strapping and lashing applications

Technical Specifications

Size	Width	Linear Break Strength (KG)	System Strength (KG)	Mtrs/Roll	Rolls/Box
Prolash 13	13	200	350	1100	2
Prolash 13 H	13	290	500	1100	2
Prolash 16	16	400	675	1700	2
Prolash 16 H	16	500	850	1700	2
Prolash 19	19	465	810	1200	2
Prolash 19 H	19	625	1100	1200	2
Prolash 25	25	800	1400	1000	2
Prolash 25 H	25	900	1500	1000	2
Prolash 32	32	1200	1950	600	2
Prolash 32 H	32	1550	2515	600	2
Prolash 34	34	1350	2200	600	2
Prolash 34 H	34	1600	2600	600	2

Tolerances: Width +/- 5%

Buckle	Qty/Box
Prolash 13 Buckle	1000
Prolash 16 Buckle	1000
Prolash 19 Buckle	1000
Prolash 25 Buckle	500
Prolash 32 Buckle	250
Prolash 34 Buckle	250



Factory Address
Plot No. G28 & G29, General Park IP,
Sultanpur Medical Devices Park,
Telangana 502 319

Corporate Address
Shantha Jubilee, Jubilee Endave,
HITEC City, Hyderabad,
Telangana 500 081

Contact +91 93939 22442
E-mail info@acmeirm.com
Website www.mvsips.com

